The Equipment Rules of Sailing

Submission: **067-11**

F.1.4(c) Hull Spars

A submission from the Chairman of the Equipment Committee

Purpose or Objective

To separate "hull spars" from other spars.

Proposal

(c) HULL SPARS

A spar attached to the hull to take rigging loads.

(i) BOWSPRIT

A hull spar extending forward to attach rigging and/or the tack of a headsail, or headsails.

(ii) BUMPKIN

A hull spar extending aft to sheet a sail and/or attach rigging.

(iii) DECK SPREADER

A hull spar extending transversely to attach standing rigging.

(d) OTHER SPARS

Other spar types include their rigging, fittings and any corrector weights, but not running rigging.

Other **Spar** Types:

(i) SPINNAKER POLE

A **spar** attached to the mast **spar** to set a spinnaker.

(ii) WHISKER POLE

A spar attached to the mast spar and a headsail clew.

(iii) BOWSPRIT

A hull spar extending forward to attach rigging and/or the tack of a headsail, or headsails.

(iv) BUMPKIN

A hull spar extending aft to sheet a sail and/or attach rigging.

(iii) GAFF

A **spar** attached at one end to a mast **spar** to set the peak, throat and/or head of a quadrilateral **sail**.

(iv) SPRIT

A **spar** attached at one end to a mast **spar** or a hull to set only the peak of a quadrilateral **sail**.

Submission: 067-11 Contd.

(v) YARD

A **spar** hoisted on a mast **spar** at a point between its ends to set the **head** of a quadrilateral sail or the **luff** of a lateen **sail**.

Current Position

As above.

Reason

To separate "hull spars" from other spars and to introduce a term that can be used in class rules to cover all such spars.