

# INTERNATIONAL DRAGON CLASS



The following amendments to the Class Rules have been approved to be effective 1<sup>st</sup> March 2012 by the Class Rules Sub Committee.

## Rule 2.346

### Amendment:

The deck shall be of timber larch, Scandinavian pine or fir, Oregon pine, spruce, or (including plywood), and may be covered with other material. The deck shall be not less than 15 14 mm thick and weighing not less than 7.6 kg/m<sup>2</sup>. 432kg/m<sup>3</sup> and be covered with canvas of not less than 236g/m<sup>2</sup> and painted, or covered with any other material of equivalent weight. Samples of the deck shall be supplied as specified in Rule 2.102.

### 2.347 Spare

The deck may be of plywood, or plywood overlaid with teak, of not less than 15mm total thickness and weighing not less than 7.6kg/m<sup>2</sup>.

## Rule 2.507 - Floors

### Amendment::

A minimum of 8 floors shall be fitted. The maximum spacing between adjacent floors shall be 700 mm. The floors may be formed as part of the internal hull moulding. The floors shall extend up to the underside of the cabin sole. No part of a floor shall extend below 1000 mm from a line joining the sheerlines unless the floors lead into and/or are parts of bulkheads. The floors shall extend up to the underside of the cabin sole.

The floors shall be of a uniform laminate of 7.5 kg/m<sup>2</sup>. The floors shall be bonded to the hull with a laminate of not less than 6 kg/m<sup>2</sup>.

Floors supporting the mast may be connected by longitudinal members. Any longitudinals shall, including any bonding flange, not extend more than 100 mm forward of station 4 or exceed 350 mm in width. The distance between the top of any longitudinal and the underside of the deck shall not be less than 650 mm.