

International Etchells CLASS



The following amendments to the Class Rules have been approved to be effective 5 March 2013.

C.5 PORTABLE EQUIPMENT

C.5 FOR USE

Rule C.5.1(a)

6 - Continuous anchor line length

Amendment: Insert : Maximum “50m”

C.5.2 NOT FOR USE

(a) MANDATORY (1)

Amendment: delete present rule and insert:

(1) “Towing rope minimum 25 m and maximum 30 m continuous length of not less than 12 mm in diameter.

Towing rope must be of a floatable material.

(N.B. Running rigging does not comply with this rule).”

C.9 Rig

C.9.2 FITTINGS

(a) USE (1)

Amendment: delete present rule and insert:

“Fore and aft mast chocks may be fitted and used to hold the mast in position in the partners.”

(2)

Amendment: delete present rule and insert:

“Mechanical means, including rams, levers and/or block and tackle arrangements with cleats, shall be permitted to move and hold the position of the mast fore and aft in the partners, provided such systems attach to the mast and fit entirely below the top of the partners.”

G.4 HEADSAIL

G.4.3 DIMENSIONS

Amendment: insert:

	Minimum	maximum
“Seven-eighths width taken as the shortest distance to the luff from the point on the leech equidistant from the head point and the three-quarter leech point ”	“315mm”	

END
