## INTERNATIONAL FINN ASSOCIATION



The following amendments to the Class Rules have been approved to be effective 1<sup>st</sup> March 2007.

#### Rule A.15.3 OLD BOATS

Amendment: Insert after "centreboard weight,": "rudder hangings"

Rule C.8.4 RUDDER. Delete Rudder attachment Dimensions entirely (for new boats, they are included in Sections D and F; For Existing Equipment, refer to A.15 and Page 2 of the Rules).

#### Amendment:

Delete (a) Dimensions

Renumber (b) Use to become (a) Use

#### Rule D.9.1. Assembled Hull

**Amendment:** add additional hull dimensions

	minimum	maximum
Bearing at Transom Pintle above hull datum point	52 mm	57 mm
Bearing at Transom Gudgeon above hull datum poin	262 mm	267mm
Axis of Transom Pintle aft of Station 0 (α)	10 mm	30 mm
Axis of Transom Gudgeon aft of Station 0 (β)	10 mm	30 mm
Difference between $(\alpha)$ and $(\beta)$		2 mm
Diameter of Pintle and of Gudgeon Hole	7.9 mm	8.1 mm

#### Rule E.3.1. (b) Rudder Assembly

**Amendment:** replace existing rule with:

"(b) The leading edge above point "k" is a line passing through point "k", running parallel to the main axis of the **rudder** gudgeon and pintle upwards to deck level."

## Rule E.3.4. Rudder Assembly

Amendment: add additional rudder dimensions

	minimum	maximum
Bearing at Rudder Gudgeon above point "k"	52 mm	57 mm
Bearing at Rudder Pintle above point "k"	262 mm	267 mm
Point k aft from Axis of Rudder Gudgeon and Pintle	10 mm	15 mm
Diameter of Gudgeon Hole and of Pintle	7.9 mm	8.1 mm

### New Rule:

Rule F.3.3 CONSTRUCTION

The **boom spar** shall include a sail groove.

Renumber Rules F.3.3 - 5 as F.3.4 - 6

# INTERNATIONAL FINN ASSOCIATION



Rule F.3.5 Dimensions (as renumbered)

**Amendment:** add additional boom dimensions

Rule G.1.7 (a) Construction

Amendment: Add to the end of the existing rule ", with luff rope and foot rope."

Rule G.1.7 (d) Construction

**Amendment:** Delete from the list of permitted fittings bolt ropes, zip fasteners,

alternative foot ropes

Rule G.1.8 Dimensions

New Rule:

Distance from **Head Point** to any part of the sail ......6050 mm max

Rule G.1.8 Dimensions

Amendment: add additional sail dimensions

Clew point to:

aft end of **foot** rope ......150 mm max

forward end of **foot** rope .................................. 2500 mm min