



The following amendments to the Class Rules have been approved to be effective 24<sup>th</sup> February 2009.

Current rule:

~~C.8.2 b) There shall be four **batten pockets** in the **leech**. One batten is permitted in each **batten pocket**, except that two battens are permitted in the uppermost **batten pocket**. The uppermost **batten pocket** may be constructed to have two separate batten insertion openings.~~

New rule:

C.8.2 b) i) MAINSAIL

The number of battens in each batten pocket is unrestricted.

ii) HEADSAIL

Only one batten is permitted in each batten pocket.

Add new rule and re-numbering:

**G.2 Definitions**

G.2.1 BATTEN POCKET

Additional **ply** to form a pocket for a batten or battens.

Current rule:

G.3.2.5 Only four batten pockets shall be permitted in the **leech**

New rule:

G.4.2.5 Only four batten pockets **as defined in G.2.1** shall be permitted in the **leech**

Current rule:

G.4.5 Only two battens shall be permitted.

~~**Batten pocket length: Inside** ..... 330 mm~~

~~**Batten pocket width: Inside** ..... 60 mm~~

Amended rule:

G.5.5 Only two batten pockets as defined in G.2.1 shall be permitted in the **leech**

G.5.6	Batten pockets.	<u>minimum</u>	<u>maximum</u>
	a) <b>Head point</b> to intersection of <b>leech</b> and centreline of uppermost batten pocket	1950	mm
	2295 mm		
	b) <b>Clew point</b> to intersection of <b>leech</b> and centreline of lower batten pocket	2070 mm	2290 mm
	<b>Batten pocket length: Inside</b> .....		330 mm
	<b>Batten pocket width: Inside</b> .....		60 mm