

## SONAR CLASS ASSOCIATION

The following amendments to the Class Rules have been approved to be effective 1<sup>st</sup> March 2003.

### Rule - Advertising

**Amendment:** Subject to approval January 2003.

### Rule G.6.2 (I)

**Amendment:** Add dimension as follows:

Foot Median..... "Maximum  
7000 mm"

## New Class Rules

### C.8 SAILS

**Amendment:** Add new class rules as follows:

#### "C.8.1 IDENTIFICATION

- (a) **Sails** shall carry identification as prescribed in section G.
- (b) Except to the extent permitted in By-Laws B 12.01, the sail number shall comply with rule A.11.2.

#### C.8.2 DIMENSIONS

The **sail** dimensions shall comply with section G.

#### C.8.3 MAINTENANCE

Routine maintenance such as cleaning or repair of damaged panels is permitted without re-measurement or re-certification.

#### C.8.4 LIMITATIONS

- (a) Not more than one mainsail, two jibs and two spinnakers shall be carried aboard while *racing*.
- (b) Not more than one mainsail, two jibs and two spinnakers shall be used during a sanctioned event, except when a **sail** has been lost or damaged beyond repair. Such replacement may be made only with the consent of the jury.

#### C.8.5 SETTING

**Sails** shall be hoisted on a halyard. The arrangement shall permit hoisting and lowering of the **sails** at sea.

##### (a) **Mainsail**

- (i) The highest visible point of the **sail**, projected at 90° to the **mast spar**, shall not be set above the **upper point**. The intersection of the leech and the top of the **boom spar**, each extended as necessary, shall not be aft of the **outer point**.

- (ii) **Luff** and **foot** boltropes shall be in the **spar** grooves or tracks.

##### (b) **Jib**

The lowest point of the **tack** when hoisted shall be less than 65 mm from the deck.

##### (c) **Spinnaker**

Only one **sail** shall be set at any time.

