



INTERNATIONAL ENTERPRISE CLASS ASSOCIATION

The following amendments to the Class Rules have been approved to be effective 13/05/13

1 Current Rule:

18.B

(9) Mainsheet attachment to transom (See also Rule 13)

~~(a) If a mainsheet horse is fitted the type shall be optional provided that Rule 13 is not contravened, but if in excess of 305 mm in length it shall be of the internal track type, secured directly to the top of the transom and may have adjustable stops, control lines, fairleads and cleats.~~

~~(b) If mainsheet eyes are fitted on the transom they shall be 230mm each side of the centre-line of the boat.~~

Amended Rule:

(9) Mainsheet **rigging shall be attached to the top face of the transom.**

2 Current Rule:

18.G

~~(3) A foresail tack distance piece without mechanical adjustment.~~

Amended Rule:

18.G

(3) **A mainsail or foresail tack attachment without mechanical adjustment**

3 Current Rule:

19.2.1.4 The following are permitted: Stitching, glue tapes, bolt ropes, elasticated bolt rope in the *foot*, corner eyes, headboard with fixings, cunningham eye/pulley, batten pocket elastic, a mast and a boom slide, leech line with cleat on leech, one ~~window located below the half width measurement~~, sailmaker label, royalty label, tell-tales.

~~19.2.1.5 There shall be no hollows in the leech.~~

Amended Rule:

19.2.1.4 The following are permitted: Stitching, glue tapes, bolt ropes, elasticated bolt rope in the *foot*, corner eyes, headboard with fixings, cunningham eye/pulley, batten pocket elastic, a mast and a boom slide, leech line with cleat on leech, one **or more windows located either less than 1000mm above the foot and/or more than 1200mm above the foot**, sailmaker label, royalty label, tell-tales.

4 Current Rule:
19.2.2 DIMENSIONS

Window internal dimension 458 mm

Amended Rule:

All windows located less than 1000mm above the foot shall fit within a rectangle of diagonal	950
All windows located more than 1200mm above the foot shall fit within a rectangle of diagonal	540

5 Current Rule:

19.3.1.3 The following are permitted: Stitching, glue tapes, corner eyes, hanks, one window located below *half width*, sailmaker label, royalty label, tell-tales.

Amended Rule:

19.3.1.3 The following are permitted: Stitching, glue tapes, corner eyes, hanks, one **or more** windows located below *half width*, sailmaker label, royalty label, tell-tales.

6 Current Rule:

19.3.2 DIMENSIONS

Window internal dimension 458 mm

Amended Rule:

19.3.2 DIMENSIONS

All windows shall fit within a rectangle of diagonal	670
--	-----

7 Current Rule:

19.3.2 DIMENSIONS

Either rig		
Top width		35
Primary reinforcement		300
Secondary reinforcement		
from Corner measurement points		900

Amended Rule:

Either rig		
Top width		35
Primary reinforcement		300
Secondary reinforcement		
from Corner measurement points		900
For Flutter patches		100