

## **INTERNATIONAL J/24 CLASS**

The following amendments to the Class Rules have been approved to be effective 1<sup>st</sup> March 2001, except Rule 2.6.1 Advertising, which is to be effective 1<sup>st</sup> January 2001.

### **Rule 3.6.5**

**Amendment:** Delete the existing rule and insert the following: "Sails may have primary reinforcing of any flexible material or coating at a corner, at Cunningham holes and at reefing points and secondary reinforcement of additional layers of cloth of weight each not greater than the body of the sail. Reinforcement, finishing materials or coatings applied to the reinforcement shall be capable of being folded in any direction without damaging the fibers. "

### **Mainsail Measurement**

#### **APPENDIX A**

**Amendment:** Add the following two definitions to the notes of the APPENDIX A; J 24 Mainsail Measurement:

- “. Width measurements shall be taken from a point on the leech, or from a point on a line bridging any hollows in the leech to the nearest point on the luff.
2. The mainsail bolt rope attachment to the boom shall be continuous and measure not less than 2300mm.”

### **Advertising**

#### **Rule 2.6.1**

**Amendment:** The Class accepts the ISAF definition of Category C with the following restrictions:

1. A maximum of three (3) advertisers be allowed per boat.
2. Advertisements are restricted to the aft 75% of the hull.
3. Advertising restricted to the lower 1/3 of the mainsail. Advertisements shall be permitted on the spinnaker with the restrictions provided by ISAF.
4. Boats may display one advertising entity on each side of the main boom.”